



Innovating Radiation Detection Technologies Since 1992

WRIST GAMMA INDICATOR PM1208M



The PM1208M Wristwatch Gamma Radiation Indicator is the next generation of the well-known PM1208 series of wrist gamma radiation dosimeters.

The PM1208 series of dosimeters have proven to be effective, accurate and dependable instruments. They are often instruments of choice when 24/7 of the radiation environment and acute dose is required and have been deployed all around the world.

The PM1208 Wristwatch Gamma radiation Indicator incorporates a sensitive Geiger-Muller gamma detector with a stylish wristwatch, combining a leading edge dosimeter technology with Swiss tradition of the watch making. An audible alarm alerts the user when a potential radiation hazard exceeds adjustable radiation threshold levels. The instrument contains non-volatile memory to keep the measured data until they are downloaded to a PC via built-in IR interface.



Main features:

- Stylish design combined with professional grade dosimeter
- Indicates dose/dose rate and dose accumulation time
- Audible alarm when preset adjustable radiation thresholds are exceeded
- Logs data in internal non-volatile memory up to 500 data points
- Communicates with a PC via a built-in IR channel
- Full wristwatch functionality: time and alarm clock functionality
- Independently displays time on digital display and analog faceplate
- Electroluminescent backlight
- Water resistant up to 100m
- Two-level battery voltage control



ALARM



MEASUREMENT

IRDA

CE **ISO 9001**

The PM1208M is a perfect combination of comfort, effectiveness and modern design which is capable to protect you and those you are care about. You will wear it everywhere: at home, at work, on the travel and even under the water.



WRIST GAMMA INDICATOR

PM1208M

SPECIFICATIONS

Detector	Geiger-Muller tube
Dose equivalent rate (DER) registration and indication range	0.01-9999,99 µSv/h
DER threshold range Step	0.01-9999.99 µSv/h 0.01; 0.1; 1; 10; 100
Accuracy of DER in the range 0.1-9999.99 µSv/h, no less	±20%
Dose equivalent (DE) registration and indication range	0.001-9999.999 mSv
DE threshold range Step	0.001-9999 mSv 0.001; 0.01; 0.1; 1; 10; 100
Accuracy of DE in the range 0.01-9999,999 mSv, no less	±20%
Energy range	0.06-1.5 MeV
PC communication	IrDA (57.6 kb/s)
Quartz watch movement	Ronda 763
Electronic quartz watch movement accuracy under normal conditions	±1 s/h
Operating conditions	Temperature 0 °C to +45 °C RH up to 95 % (40 °C)
Case Protection Class	IP68
Power supply	Lithium battery CR 2032
Battery lifetime (typical)	18 months
Water resistant	up to 100 m
Dimensions	50x45x20 mm
Weight (without bangle)	100 g max.

Design and specifications of the device can be changed without further notice.

PM1208M meets most relevant parts of IEC 60846 standard

Sales North and South America

Polimaster Inc.
2300 Clarendon Boulevard, Suite 708
Arlington VA, 22201, USA
Phone: +1 703 525-5075
Fax: +1 703 525-5079
E-mail: info@polimaster.us

Sales Europe

Polimaster Instruments UAB
125, Kalvariju St., 3P3/p building,
Vilnius, LT-08221, Republic of Lithuania
Phone: +370 5 210 23 23
Fax: +370 5 210 23 22
E-mail: polimaster@polimaster.lt

Sales Asia, Africa, Australia and Oceania

Polimaster Ltd.
112, Bogdanovich St.,
Minsk, 220040, Republic of Belarus
Phone: +375 17 217 70 80
Fax: +375 17 217 70 81
E-mail: polimaster@polimaster.com