

AT6101C, AT6101CM Spectrometers

Backpack-type Radiation Detector



BDKG-11M (γ)
[AT6101C]

BDKG-19M (γ)
[AT6101CM]

BDKG-04 (X, γ)

BDKN-05 (n)

AT6101C Spectrometer is designed for detection of radioactive sources and is an efficient tool for prevention of radiological terrorist threats and other unauthorized activities like illicit storage, use, transfer and traffic of radioactive substances and materials. Can also be used for radiation monitoring of areas, routes, isolated grounds, industrial sites and buildings with GPS-referencing of measurement data.

The spectrometer can comprise the following detection units:

- BDKG-11M / BDKG-19M Spectrometric gamma radiation detection unit (basic version)
- BDKN-05 Neutron radiation detection unit (option).
- BDKG-04 Wide-range dosimetric gamma radiation detection unit (option).

In cases when higher spectrometer sensitivity to gamma radiation is required BDKN-05 detection unit can be replaced by additional BDKG-11M (BDKG-19M) detection unit (option).

The spectrometer can be delivered in a backpack (basic version) or in a sealed shock-proof case (option).

Operating principle



As a control and indication device the handheld computer (HPC) is used. Data transfer from detection units to HPC is carried out via Bluetooth. Data transfer by cable is carried out in the places where transfer via radiochannel is impossible or undesirable.

The spectrometer operates in continuous radiation environment scan mode: continuous search, detection, localization and identification of gamma radiation sources; search and detection of neutron radiation sources. When radioactive source is detected the spectrometer activates alarm and identifies its radionuclide composition.

Types of identified radionuclides are displayed on HPC screen and operator hears a corresponding voice message in a wireless headset.

Measurement results are continuously transmitted into HPC for subsequent processing by PC and can be plotted onto a map using application software tools.



Version of AT6101C
in shock-proof case

Applications

- Radioactive substances and materials traffic control
- Radioactive contamination monitoring of areas by mobile tools
- Public events radiation safety control
- Radiation protective measures in case of nuclear disasters
- Radiation monitoring of facilities and sites
- Dosimetric and spectrometric survey of ground and facilities, radioactive mapping

Key users

- Organizations for nuclear energy use control
- Security service
- Customs service
- Border control service
- Radiation monitoring service
- Emergency rescue squads

Features

- Automatic simultaneous gamma-neutron radiation scanning
- Search, detection and localization of radioactive source and real-time identification of its isotopic composition
- Automatic accommodation to radiation background level change
- Dose rate measurement range can be expanded to 10 Sv/h
- Simultaneous measurement of gamma radiation spectral distribution and dose rate
- Scanning data are constantly recorded for further analysis
- Measurement results can be tied to a location (GPS function)
- "GARM" application software for further data processing and analysis in expert mode
- "ARMS" application software (option) for automatic data transfer to a remote server (Over FTP server and if HPC has a 3G communication function or can be connected to a Wi-Fi network)
- 20 hours of operation time
- 130 hours memory capacity
- Minimum weight in its class



ATOMTEX[®]

INSTRUMENTS AND TECHNOLOGIES FOR NUCLEAR
MEASUREMENTS AND RADIATION MONITORING

AT6101C, AT6101CM Spectrometers

Specification	AT6101C	AT6101CM
GAMMA RADIATION DETECTION UNIT	BDKG-11M (1 / 2 pcs.)	BDKG-19M (1 / 2 pcs.)
Gamma radiation detector	Scintillator, NaI(Tl) Ø63x63 mm	Scintillator, NaI(Tl) Ø63x160 mm
Energy range In Spectrometric mode In Dosimetric mode	20 keV...3 MeV 50 keV...3 MeV	
Ambient gamma radiation dose equivalent rate measurement range	0.01...150 µSv/h	0.01...50 µSv/h
Intrinsic relative error of dose rate measurement	±20% max.	
Sensitivity to gamma radiation, not less ²⁴¹ Am ¹³⁷ Cs ⁶⁰ Co	cps/µSv·h ⁻¹ 13500 (27000)* 2200 (4400)* 1200 (2400)*	cps/µSv·h ⁻¹ 37000 (74000)* 6000 (12000)* 2500 (5000)*
Radionuclide identification	Medical, Industrial, Natural, Bremsstrahlung (Individual order: Library of identified radionuclides can be corrected)	
Minimal detectable level of gamma radiation dose rate from a source, moving at 0.5 m/s	0.05 µSv/h (0.035 µSv/h)*	0.03 µSv/h (0.02 µSv/h)*
Minimal activity of ¹³⁷Cs source, detectable at the distance of 1 m in a time ≤2 s. 95% probability of source detection with false alarm frequency not above 1 in 10 minutes	(450±10) kBq	(300±10) kBq
Alarm response time	<2 s	
Typical resolution at 662 keV (¹³⁷Cs)	7.5%	8%
Number of ADC channels	1024	1024
Maximum input statistical load	10 ⁵ s ⁻¹ (≥2·10 ⁵ s ⁻¹)*	10 ⁵ s ⁻¹ (≥2·10 ⁵ s ⁻¹)*
<i>* Configuration with two BDKG-11M (BDKG-19M) detection units</i>		
GAMMA RADIATION DETECTION UNIT	BDKG-04	
Purpose	Additional accessory for expanding dose rate measurement range of X-ray and gamma radiation (Up to 10 Sv/h)	
NEUTRON RADIATION DETECTION UNIT	BDKN-05 **	
Neutron radiation detector	2 proportional counters ³ He Ø30x360mm in a polyethylene moderator	
Energy range	0.025 eV...14 MeV	
Sensitivity to ²⁵²Cf neutron radiation	20 cm ²	
Minimal activity of Pu-Be source, detectable at the distance of 1.25 m in a time ≤3 s. 95% probability of source detection with false alarm frequency not above 1 in 60 minutes	(5±1.25)·10 ⁴ neutron/s	
<i>** Not available for onfiguration with two BDKG-11M /BDKG-19M detection units</i>		
Other parameters and operating conditions		
GPS	GPS-receiver, integrated into HPC. Positioning accuracy ≥3 m	
Burn-up life	≥100 Sv	
Protection class backpack version shock-proof case version	IP54 IP65	
Continuous run time	~20 h	
Working temperature range	-20°C...+50°C	
Relative humidity	≤95% (with air temperature ≤35°C without condensation)	
Overall dimensions backpack version shock-proof case version	450x330x250 mm 625x500x300 mm	500x330x250 mm 625x500x300 mm
Weight*** backpack version shock-proof case version	7 kg 17 kg	8.5 kg 18.5 kg
<i>*** Configuration with BDKG-11M /BDKG-19M, BDKG-04 and BDKN-05 detection units</i>		

Design and specifications are subject to change without notice

Spectrometers meet IAEA requirements (technical and functional specifications for border monitoring equipment); ANSI 42.43 standard requirements; Safety standard requirements: IEC 61010-1:2001; EMC requirements: EN 55011:2009, IEC 61000-4-2:2008, IEC 61000-4-3:2008.



ATOMTEX®

<http://www.atomtex.com>

5, Gikalo st., 220005 Minsk,
Republic of Belarus
Tel./fax: +375 17 2928142
E-mail: info@atomtex.com



Corporate Member
of European
Nuclear
Society